

Technical sheet :

GENERAL PURPOSE BUCKET ESSENTIAL



Benefits







- A bucket for all construction applications.
- Dedicated to heavy bulk: sand, earth, stones, gravels, etc.
- Tested at the R&D Center on high demanding applications.
- Designed and validated by Manitou.

Technical characteristics

- Capacity: 800 up to 1000L.
- For material density up to 2100 kg/m³.
- Simplified structure with straight sides.
- Integrated level indicator.
- No side strengthener.

Technical characteristics		BGP 1500 / 400 Essential	BGP 2000 / 800 Essential	BGP 2450 / 1000 Essential
Distance to center of gravity (mm)		228	283	297
Capacities				
Heaped Capacity (l)		394	802	995
Struck capacity (l)		311	622	766
Weight and dimensions				
Overall height (mm)	h17	625	786	786
Width (mm)		1500	2000	2450
Length (mm)		812	925	925
Depth (mm)	p5	627	817	817
Overall weight (kg)		161	345	397
Working Parameters				
Machine Equipement		×	×	×
Hydraulic system		No	No	No
Flexible tube		-	No	-
Other Data for Attachments				
Carriage type		-	Manitou	-

Machines compatibility		BGP 1500 / 400 Essential	BGP 2000 / 800 Essential	BGP 2450 / 1000 Essential
Reference number		-	52688160	52658055
All-Tach®		52702290	-	-
4 point Carriage		52723638	-	-
Euro Carriage		52723639	-	-
GCT 3-14		X	-	-
GCT 3-14 +		X	-	-
MLT 635-130 PS+		-	-	X
MLT 635-140 V+		-	-	X
MLT 733-115		-	-	X
MLT 733-115 LSU		-	-	X
MLT 737-130 PS+		-	-	X
MLT 741-130 PS+		-	-	X
MLT 741-140 V+		-	-	X
MLT 841-145 PS+		-	-	X
MLT 940-140 V+		-	-	X
MLT 1041-145 PS+L		-	-	X
MLFX 732		-	-	X
MLFX 735 T LSU		-	-	X
MLFX 735 T LSU (70 KW)		-	-	X
MLFX 1035 LT LSU		-	-	X
MT 730 H		-	X	-
MT 733 Easy		-	-	X
MT 930 H		-	X	-
MT 930 HA		-	X	-
MT 933 Easy		-	-	X
MT 1135 easy ST5		-	-	X
MT 1135 H easy ST5		-	-	X
MT 1135 HA Easy ST5		-	-	X
MT 1135 ST5		-	-	X
MT 1335		-	-	X
MT 1335 easy ST5		-	-	X
MT 1335 H easy ST5		-	-	X
MT 1335 HA easy ST5		-	-	X
MT 1335 ST5		-	-	X
MT 1440 A ST5		-	-	X
MT 1440 easy ST5		-	-	X
MT 1440 HA ST5		-	-	X
MT 1440 ST5		-	-	X
MT 1840 A ST5		-	-	X
MT 1840 easy ST5		-	-	X
MT 1840 HA ST5		-	-	X
MT 1840 ST5		-	-	X
MTX 733		-	-	X
MTX 1033		-	-	X
MTX 1440		-	-	X
MTX 1440 A		-	-	X
MTX 1840		-	-	X
MTX 1840 A		-	-	X
ULM 412 H		X	-	-
ULM 412 H		X	-	-
ULM 415 H		X	-	-
ULM 415 H		X	-	-
MLT 733-115 ST4 OLD		-	-	X
MLT 737-130 PS+ ST4 OLD		-	-	X
MT 1033 easy OLD		-	-	X
MT 1440 OLD		-	-	X

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



Siège Social
430 rue de l'Aubinière - 44150 Ancenis Cedex - France
Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97
www.manitou.com



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes