Technical sheet :

## PICKUP SWEEPER



## **Benefits**

- High output attachment for the most demanding applications.
- Sweep and pick-up in one operation.
- Up to 2500 m<sup>2</sup> cleaned in 10 minutes.
- High quality sweeping on uneven ground.
- Interchangeable side brush (right or left) for a perfect sweeping along wall and sidewalks.

## **Technical characteristics**

- Floating frame which avoids any squashing the attachment when driving on the bumpy road.
- ø 230 mm side brush in polyester and galvanized steel.
- Synchronisation valve: sweep and control the dirt tank with 1 single hydraulic function.
- Pressure limiter for powerful machine.
- Brush ø 600 mm.
- 4x ø 200 mm heavy duty wheels.
- Recommended option: continuous hydraulic flow.



Pickup Sweeper - Created on May 24, 2022 at 8:48:58 AM UTC

Technical characteristics		BRB 1600	BRB 2200	BRB 2500
Distance to center of gravity (mm)		1050	1050	1050
Capacities				
Heaped Capacity (I)		380	530	600
Weight and dimensions				
Overall height (mm)	h17	1068	1068	1068
Width (mm)		2000	2600	2900
Length (mm)		2370	2370	2370
Overall weight (kg)		775	925	1000
Working Parameters				
Machine Equipement		ee er		FF FL
		TT LE	YY LE	ΥΥ LL
Machines compatibility		BRB 1600	BRB 2200	BRB 2500
Reference number		790313	790315	790316
MLT 625-75 H		Х		
MLT 635-130 PS+			X	
MLT 635-140 V+			X	
MLT 737-130 PS+ ST4		-	x	
MLT 840-145 PS+		-	X	
MLT 841-145 PS+			X	
MLT 961-145 V+ L			X	X
MLT 961-160 V+ L		-	X	
MLT 1041-145 PS+L			X	
MLT-X 625-75 H		X		
MLT-X 735 T LSU			X	
MLT-X 840-140 PS+			X	
MLT-X 841 - 145 PS+			X	
MLT-X 961-145 V+ L			X	X
MLT-X 961-160 V+ L			X	
MLT-X 1041-145 PS+L			X	
MT 625 HA		x		
MT-X 625 H		Х		

TABLE SYMBOL							
$\times$	No predisposition required	各各	Hydraulic line		Return piping to hydraulic oil tank		
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition		



Siège Social 430 rue de l'Aubinière - 44150 Ancenis Cedex - France Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97 www.manitou.com



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in thisbrochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes